

Refrigeration Tube



Outside Diameter mm	Wall Thickness mm	Weight kg/m	Product No.
4.76	0.71	0.08	0002346
6.35	0.71	0.11	0002347
7.94	0.71	0.14	0002348
9.52	0.71	0.18	0002349
12.70	0.71	0.24	0002350
15.90	0.89	0.37	0002351
19.10	0.89	0.46	0002352

Available in coils (annealed) for O.D sizes between 4.76mm and 19.1mm

Available in lengths (hard drawn) for O.D. sizes between 9.52mm and 79.4mm

Engineering Tube Indent Only

Alloy 122 - Hard Drawn



Outside Diameter mm	Wall Thickness mm	Weight kg/m	Product No.
6.35	1.63	0.21	0002330
19.05	1.63	0.79	0002333
25.40	1.22	0.82	0002338
38.10	1.22	1.09	0002341

Alloy 122

Hard Drawn

Length

5m or 6m

Domestic Copper Tube

(NZS 3501:1976)
Alloy 122 - Half Hard



Nominal Bore mm	Wall Thickness mm	Weight kg/m	Product No.
15.0	0.70	0.28	0011191
20.0	0.90	0.51	0011194
15.0	1.02	0.39	0011189
20.0	1.02	0.57	0011192
25.0	1.02	0.74	0011195
32.0	1.22	1.12	0004638
40.0	1.22	1.35	0004639
50.0	1.22	1.78	0004640
65.0	1.22	2.20	0004641
80.0	1.42	3.12	0004642
100.0	1.63	4.69	0004643
150.0	1.83	7.86	0004644

Length 5m